



The product shown may differ from standard configuration.

PRIMO[®] L

Standard Seat with Pneumatic Suspension



PRIMO® L

Technical data

Standard seat

This seat's reduced-travel pneumatic suspension, which runs on a 12 V or 24 V power source, effectively attenuates vibrations in even the tiniest cabs. It can be optimally set to the operator's weight using an ergonomically placed crank, aided by an indicator. The seat meets the latest safety requirements and is equipped with a seat and belt contact switch as well as a duosensitive ELR-belt system with orange belt straps as standard. Additionally, the Primo L features an individually adjustable, mechanical lumbar support.



Pneumatic suspension



Mechanical lumbar support



Pneumatic weight adjustment

Features

	PRIMO® L
ARTICLE NO.	
Fabric, compressor 12V	1564039
Fabric, compressor 24V	1564041
Imitation leather, compressor 12V	1564040
STANDARD FEATURES	
Shock absorber, nonadjustable	●
Pneumatic suspension with 12 V/24 V compressor	●
Suspension stroke, 60 mm	●
1 Height adjustment, 20 mm	●
2 Weight adjustment, pneumatic, 45-170 kg	●
3 Fore/aft adjustment, 210 mm	●
4 Lumbar support, mechanical	●
5 Adjustable backrest angle	●

	PRIMO® L
6 ELR belt system, duosensitive, orange belt	●
Belt buckle with contact switch	●
Seat cushion width	470 mm
Operator presence switch (OPS)	●
OPTIONAL FEATURES	
7 Document box	○
8 Armrests, adjustable angle, 60 mm x 320 mm	○
Fore/aft isolator*	○
9 Backrest extension, integrated	○
10 Seat heating	○

* Fore/aft isolator not for earth-moving machinery

Measurements (installation dimensions)

