



The product shown may differ from standard configuration.

PRIMO® M

Standard Seat with Mechanical Suspension



PRIMO® M

Technical data

Standard seat

This seat’s mechanical suspension with reduced suspension travel of 60 mm effectively buffers vibrations in even the smallest cabs. The upper seat section is designed to deliver comfort from the word go. The focus is on the most important adjustments, including a mechanical lumbar support and mechanical weight setting feature. The seat meets the latest safety requirements and is equipped with a belt contact switch as well as a duosensitive ELR-belt system with orange belt straps as standard.



Mechanical suspension



Mechanical lumbar support



Manual weight adjustment

Features


ARTICLE NO.	PRIMO® M
Fabric	1564042
Imitation leather	1564043
STANDARD FEATURES	
Shock absorber, nonadjustable	●
Suspension, mechanical	●
Suspension stroke , 60 mm	●
1 Weight adjustment, manual, 45-170 kg	●
2 Fore/aft adjustment, 210 mm	●
3 Lumbar support, mechanical	●
4 Adjustable backrest angle	●

	PRIMO® M
Seat cushion width	470 mm
5 ELR belt system, duosensitive, orange belt	●
Belt buckle with contact switch	●
OPTIONAL FEATURES	
6 Document box	○
7 Armrests, adjustable angle, 60 mm x 320 mm	○
Fore/aft isolator*	○
8 Backrest extension, integrated	○
9 Seat heating	○
Operator presence switch (OPS)	○

* Fore/aft isolator not for earth-moving machinery

Measurements (installation dimensions)

● STANDARD FEATURES ○ OPTIONAL FEATURES



All dimensions in mm.
Subject to technical changes.